PROFESSIONAL PARQUET FLOORING ADHESIVE

DESCRIPTION: Torcan Professional Flooring Adhesive is a non-flammable adhesive for the indoor gluing of parquet flooring on floors made of plywood, wood, well cured concrete either above or below grade. It is not recommended for pre-finished parquet flooring.

PHYSICAL PROPERTIES:

- Viscosity 18-22 cps (6/20rpm 25°c)
- Solids 50 ± 1%
- pH 6.5 7.0
- Colour Creamy yellow
- Specific Gravity 1.11 1.15
- Water Resistance Excellent (when dry)
- Open Time 30 minutes (depending on trowel, temperature and humidity)
- Shelf Life 1 year at room temperature
- Clean Up Water

SURFACE PREPARATION: Floor surface must be dry, clean, free of dust, oil, grease or any foreign matter. It must also be, or be made, porous (if in doubt, try soaking the surface with a small amount of water). If painted or varnished, it must be sanded completely.

If the surface is likely to retain moisture (especially a concrete floor below grade) a sub-floor should be built.

APPLICATION: Keep the adhesive, the floor covering and the floor surface at more than 18°c before, during and after application.

Use a 5mm (3/16") notched trowel. Do not apply more adhesive that can be covered in 10 minutes. Leave a minimum expansion space of 0.65 (1/4") wide next to walls and around fixed objects.

Let the adhesive dry for 24 hours before washing the installation, allowing any heavy foot traffic or replacing any furniture.

COVERAGE: 1 litre covers approximately 2m2 (with a 5mm (3/16") trowel).

FREEZE/THAW STABILITY: If frozen up to -10°c, allow the adhesive to thaw to room temperature and stir before using.

CLEAN-UP: Excess adhesive should be removed while still fresh with a damp cloth and the tools can be cleaned with water. Mineral spirits may be used to remove dried adhesive.

RECOMMENDATIONS: This adhesive is not recommended for the installation of pre-finished parquet. Rather use our Rapid Set Parquet Flooring Adhesive.

Our personnel are available to purchasers to obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

Torcan Coatings Inc. 14 Oakland Ave. Toronto, Ontario. M9M 2H8